

LUCTRA® VITAWORK® 17 Asym. PIR (Art.-Nr.: 9249-140)



LED free-standing luminaire for visual comfort (ergonomic LED free-standing luminaire), double asymmetrical, direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, double asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; asymmetrical light distribution for illuminating deep rooms.

Illuminants: LED; luminous flux approx 15,758 lm, power consumption approx 123 W, effective light output >140 lm/W, 4,000 K, colour rendering CRI ≥ 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50.000 hours; power supply length 3 m and Schuko-Plug; Stand-by consumption ≤ 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive plastic touch control panel with patented VITACORE® electronics, with switchable infrared presence and light intensity sensors, optimised for height-adjustable desks.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, base C-shaped made of steel, base surface: metallic silver; dimensions: H 2,040 mm; clear height > 2m

CE, protection class I, protection class IP20

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu

LUCTRA® VITAWORK® 17 Asym. PIR (Art.-Nr.: 9269-140)



LED free-standing luminaire for visual comfort (ergonomic LED free-standing luminaire), double asymmetrical, direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, double asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; asymmetrical light distribution for illuminating deep rooms.

Illuminants: LED; luminous flux approx 15,758 lm, power consumption approx 123 W, effective light output >140 lm/W, 4,000 K, colour rendering CRI ≥ 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50.000 hours; power supply length 3 m and Kettle Plug; Stand-by consumption ≤ 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive plastic touch control panel with patented VITACORE® electronics, with switchable infrared presence and light intensity sensors, optimised for height-adjustable desks.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, base C-shaped made of steel, base surface: metallic silver; dimensions: H 2,040 mm; clear height > 2m

CE, protection class I, protection class IP20

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu

LUCTRA® VITAWORK® 17 Asym. DIM (Art.-Nr.: 9253-140)



LED free-standing luminaire for visual comfort (ergonomic LED free-standing luminaire), double asymmetrical, direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, double asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; asymmetrical light distribution for illuminating deep rooms.

Illuminants: LED; luminous flux approx 15,758 lm, power consumption approx 123 W, effective light output >140 lm/W, 4,000 K, colour rendering CRI ≥ 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50.000 hours; power supply length 3 m and Schuko-Plug; Stand-by consumption ≤ 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive plastic touch control panel with patented VITACORE® electronics.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, base C-shaped made of steel, base surface: metallic silver; dimensions: H 2,040 mm; clear height > 2m

CE, protection class I, protection class IP20

Certification: GS, ENEC

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77–79 · 58636 Iserlohn
Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu

LUCTRA® VITAWORK® 17 Asym. DIM (Art.-Nr.: 9270-140)



LED free-standing luminaire for visual comfort (ergonomic LED free-standing luminaire), double asymmetrical, direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, double asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; asymmetrical light distribution for illuminating deep rooms.

Illuminants: LED; luminous flux approx 15,758 lm, power consumption approx 123 W, effective light output >140 lm/W, 4,000 K, colour rendering CRI ≥ 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50.000 hours; power supply length 3 m and Kettle Plug; Stand-by consumption ≤ 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive plastic touch control panel with patented VITACORE® electronics.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, base C-shaped made of steel, base surface: metallic silver; dimensions: H 2,040 mm; clear height > 2m

CE, protection class I, protection class IP20

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu

LUCTRA® VITAWORK® 17 Sym. PIR (Art.-Nr.: 9252-140)



LED free-standing luminaire for visual comfort (ergonomic LED free-standing luminaire), direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, double asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; symmetrical light.

Illuminants: LED; luminous flux approx 15,758 lm, power consumption approx 123 W, effective light output >140 lm/W, 4,000 K, colour rendering CRI \geq 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50.000 hours; power supply length 3 m and Schuko-Plug; Stand-by consumption \leq 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive plastic touch control panel with patented VITACORE® electronics, with switchable infrared presence and light intensity sensors, optimised for height-adjustable desks.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, base C-shaped made of steel, base surface: metallic silver; dimensions: H 2,040 mm; clear height > 2m

CE, protection class I, protection class IP20

Certification: GS, ENEC

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77–79 · 58636 Iserlohn
Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu

LUCTRA® VITAWORK® 17 Sym. PIR (Art.-Nr.: 9272-140)



LED free-standing luminaire for visual comfort (ergonomic LED free-standing luminaire), direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, double asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; symmetrical light.

Illuminants: LED; luminous flux approx 15,758 lm, power consumption approx 123 W, effective light output >140 lm/W, 4,000 K, colour rendering CRI \geq 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50.000 hours; power supply length 3 m and kettle plug; Stand-by consumption \leq 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive plastic touch control panel with patented VITACORE® electronics, with switchable infrared presence and light intensity sensors, optimised for height-adjustable desks.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, base C-shaped made of steel, base surface: metallic silver; dimensions: H 2,040 mm; clear height > 2m

CE, protection class I, protection class IP20

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu

LUCTRA® VITAWORK® 17 Sym. DIM (Art.-Nr.: 9254-140)



LED free-standing luminaire for visual comfort (ergonomic LED free-standing luminaire), direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, double asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; symmetrical light.

Illuminants: LED; luminous flux approx 15,758 lm, power consumption approx 123 W, effective light output >140 lm/W, 4,000 K, colour rendering CRI \geq 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50.000 hours; power supply length 3 m and Schuko-Plug; Stand-by consumption \leq 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive plastic touch control panel with patented VITACORE® electronics.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, base C-shaped made of steel, base surface: metallic silver; dimensions: H 2,040 mm; clear height > 2m

CE, protection class I, protection class IP20

Certification: GS, ENEC

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu

LUCTRA® VITAWORK® 17 Sym. DIM (Art.-Nr.: 9271-140)



LED free-standing luminaire for visual comfort (ergonomic LED free-standing luminaire), direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, double asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; symmetrical light.

Illuminants: LED; luminous flux approx 15,758 lm, power consumption approx 123 W, effective light output >140 lm/W, 4,000 K, colour rendering CRI \geq 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50.000 hours; power supply length 3 m and kettle plug; Stand-by consumption \leq 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive plastic touch control panel with patented VITACORE® electronics.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, base C-shaped made of steel, base surface: metallic silver; dimensions: H 2,040 mm; clear height > 2m

CE, protection class I, protection class IP20

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77-79 · 58636 Iserlohn

Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu

LUCTRA® VITAWORK® 17 Asym. PIR CLAMP (Art.-Nr.: 9255-140)



LED luminaire with table clamp for visual comfort (ergonomic LED free-standing luminaire), double asymmetrical, direct / indirect distribution

LED free-standing luminaire direct/indirect distribution, asymmetrical, luminaire head direct: with asymmetrical light guiding panel / indirect with clear diffuser; asymmetrical light distribution for illuminating deep rooms.

Illuminants: LED; luminous flux approx 15,758 lm, power consumption approx 123 W, effective light output >140 lm/W, 4,000 K, colour rendering CRI ≥ 80; colour tolerance SDCM <3; UGR <16, energy efficiency class: A++; lifetime (L85B10) > 50,000 hours; power supply length 3 m and Schuko-Plug; Stand-by consumption ≤ 0.5W.

Operation: direct and indirect components separately and continuously dimmable via the capacitive touch control panel with patented VITACORE® electronics, with switchable infrared presence and light intensity sensors, optimised for height-adjustable desks. Attachment by table clamp with a clamping range of 16-60 mm.

Luminaire head aligned transversely to mast (WxDxHxD) 542 x 370 x 32.5 mm, head surface: metallic silver, side parts: black; mast made of aluminium, mast surface: metallic silver, front cover: black, dimensions H 1,395 mm; clear height > 2m

CE, protection class I, protection class IP20

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77-79 · 58636 Iserlohn

Germany

Phone +49 2371 662-445

info@luctra.de · www.luctra.eu