

VITAWORK®



Fact Sheet

TECHNICAL DATA

| VITAWORK® 12 | | | |
|--------------------------------|---|---------------------|-----------------------|
| Colours | 140 Metallic Silver/Black (similar RAL 9006 / 7021) | | |
| Dimensions | Height: | 2,040 mm | |
| | Luminaire head (W x D x H): | 542 x 370 x 32,5 mm | |
| | Ceiling height clearance: | > 2 m | |
| Weight | 19 kg | | |
| Lamp base | C-shaped | | |
| Material | Aluminium, Steel (lamp base), Plastic (touch panel & side caps) | | |
| Energy efficiency | This product contains (a) light source(es) with the energy efficiency class(es) | | |
| | Light source direct no. 34601, energy efficiency class D (Reg. 908500) | | |
| | Light source indirect no. 34600, energy efficiency class D (Reg. 908623) | | |
| Protection type | IP 20 | | |
| Protection class | I ⚡ | | |
| | | | |
| Illuminants | | | |
| Fitted with | LED | | |
| Power consumption | 81 W | | |
| Light distribution | symmetric | | |
| Nominal luminous flux direct | 2,000 lm | | |
| Nominal luminous flux indirect | 10,000 lm | | |
| Nominal luminous flux | 12,000 lm | | |
| Luminous efficiency | > 136 lm/W | | |
| Colour temperature (CCT) | 4,000 K | | |
| Colour tolerance | < 3 SDCM | | |
| 50,000 h | L85B10 | | |
| UGR | < 16 | | |
| Colour reproduction index | > 80 | | |
| Plug | Schuko-plug (Type F) / Kettle plug + EU/CH/UK - Plug | | |
| Cable length | 3 m | | |
| Standby consumption | ≤ 0,5 W | | |
| | | | |
| VITACORE® | | | |
| Operation | via VITACORE® electronics and sensors | | |
| Light intensity setting | Seamless and in five steps direct & indirect dimming via the touch panel | | |
| Sensors | Infrared Presence Sensor & Luminosity Sensor | | |
| | | | |
| Article overview | | | |
| Article number | Luminaire | Plug | Control |
| 9243-140 | VITAWORK® 12 Sym. PIR | Schuko-plug | Dimmable plus sensors |
| 9263-140 | VITAWORK® 12 Sym. PIR KP | Kettle plug | Dimmable plus sensors |
| 9244-140 | VITAWORK® 12 Sym. DIM | Schuko-plug | Dimmable |
| 9264-140 | VITAWORK® 12 Sym. DIM KP | Kettle plug | Dimmable |




TECHNICAL VIEW



LIGHT DISTRIBUTION CURVE

VITAWORK®



Free download at www.luctra.eu

LUCTRA

LUCTRA® is a brand of
 DURABLE · Hunke & Jochheim GmbH & Co. KG
 Westfalenstraße 77-79 · 58636 Iserlohn
 Postfach 1753 · 58634 Iserlohn
 Tel.: +49 23 71 66 24 45
 info@luctra.eu · www.luctra.eu